

Voice eXchange Professional Series, a specially built IP PBX system carefully designed to cater for small to mid size business environment.

VX-100 combines with rich features and comparable with enterprise grade unified communication systems coupled with stability. System support up to 150 users with 60 concurrent calls and recordings.

System is expandable with additional main unit to allow system-interconnection for line sharing, Intercom and maximum cost saving on communication.

VX-100 is the most preferred choice to replace legacy Key Telephone Systems or small-mid size Digital PBX system.



Front



Back

Feature List:

Address Book	Direct Dialing Inward
Black List Number	Do Not Disturb
Calender	Follow Me
Conference Bridging	Flash Operator Panel 2 (Enhanced)
Call Back	Group Paging
Caller ID	Group Pick up
Call Details Report	Inbound Routes
Call Forwarding on Busy	Instant Messaging (FOP2)
Call Forwarding on No Answer	Inter-Asterisk Xchange Route
Call Forward Variable	Interactive Directory Listing
Call Parking	Interactive Voice Response -IVR
Call Pick up	Local and Remote Call Agents
Call Queues	Music On Hold
Call Queues Priority	Outbound Routes
Call Recording (Web-based)	Pin Set
Call Spying (With authentication)	Presence (FOP2)
Call Transfer (Internal External)	Ring Groups
Call Waiting	Trunks (SIP IAX FXO)
Day/Night Control	Time Conditions (Day/Night/Lunch)
Direct Inward System Access	Voice Mail (MWI Email Blasting)

VoiceMail:

- Visual Indicator for Messages
- Voice Mail to Email
- Stutter Dialtone for Message Waiting
- Web voicemail Interface

Interactive Voice Response:

- Digital Receptionist
- Extension Dialing
- Call Queues
- Call Announcement

Security Tool:

- Intrusion Prevention System
- Access Control

Protocols:

- SIP (Session Initiation Protocol)
- SCCP (Skinny Call Control Protocol)
- IAX (Inter Asterisk Xchange Protocol)

Codecs:

G.711|G.729|GSM|Ulaw|Alaw|H264

Hardware Specification

Super Micro X9SCL+F Serverboard
Intel Dual Core Xeon i3-3220 (3.3Ghz, 3MB) CPU
4 GB Memory
1 x 120GB SSD
2 x Gigabyte LAN Ports
1U Chassis (Front I/O Ports)
280W PSU c/w Rail Kit

Dimension

Height	1.7" (43mm)
Width	16.8" (426mm)
Depth	14.0" (356mm)
Gross Weight	11 lbs (5kg)
Color	Black

System Capacity

Extensions	: 150
Concurrent Calls	: 60
Concurrent Recordings	: 60
Recording Storage Life	: 180 Days
Trunk Slot	: 1
Drive Bay	: 2

System Options

- Single Span E1 Card
- Double Span E1 Card
- 4 | 8 Ports FXO Card
- 16 | 24 Ports FXO Card
- Call Recording Module

Recommended IP Phones

Below models shown is the most popular choices



ES290-PN



ES330-PEN



ES410-PEN



ESM-32



SPA303



SPA502G



SPA504G



SPA525G



SPA500S



IP 331



IP 335



IP 650



IP 650 Console

Copyrights @ DC Apex Integrators (s) Pte Ltd All rights reserved

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. DC Apex may change the information at any time without notice.

Product of:



DC Apex Integrators (S) Pte Ltd
Block 3023 Ubi Road 3
#03-11 UbiPlex 1
Singapore 408663

Tel: +65 6591 8833

Email: sales@dc-apex.com.sg
www.dc-apex.com.sg